


PRODUCT  
Colours



180  
MAYFAIR

Vinyl Plank



185  
CAMDEN

Vinyl Plank



350  
PADDINGTON

Vinyl Plank



510  
WESTMINSTER

Vinyl Plank




520  
PARK LANE

Vinyl Plank



530  
ST JAMES

Vinyl Plank



540  
IMPERIAL

Vinyl Plank



545  
COLONIAL  
BLACKBUTT

Vinyl Plank



555  
COLONIAL  
SPOTTED GUM

Vinyl Plank



560  
HIGH  
STREET

Vinyl Plank



625  
MARBLE  
ARCH

Vinyl Plank



640  
FLEET  
STREET

Vinyl Plank



710  
LANCASTER

Vinyl Plank



730  
NOTTING HILL

Vinyl Plank



750  
KENSINGTON

Vinyl Plank



780  
OXFORD

Vinyl Plank


REGENT  VINYL PLANK

Durable, easy to maintain and water resistant<sup>^</sup>, Regent vinyl planks are the perfect choice for creating a beautiful timber look throughout all areas of your home. The stunning colour palette provides a range of options to suit a variety of interiors, so you can find a warm and comfortable timber-look floor that complements your style.

Product images on this flyer should only be used as a guide or point of reference. Actual samples should be inspected at your nearest retailer to confirm texture and colour before making a purchase decision. It is also noted colour appearance can vary depending upon the type of light under which a sample is viewed and light sources where the flooring is installed. <sup>^</sup>Subject to proper installation and maintenance.

PRODUCT  
**Specifications**

**REGENT Direct Stick Plus - Vinyl Plank Product Details**

Technical Data		Technical Data	
Type	Vinyl Plank	Colours	16
Plank Thickness	4.5mm	Protective Coating	PUR + Scratch Resist
Wear Layer	0.5mm	Finish	Matte
Dimensions	1219mm (L) x 178mm (W)	Surface	Embossed
Planks per Box	10	Profile	Square Edge
M <sup>2</sup> per Box	2.17m <sup>2</sup>	M <sup>2</sup> per Pallet	119.35m <sup>2</sup>
Installation Method	Direct Stick Plus  Please refer Installation instructions for further details		



Performance								
Classification	23, 32				ISO 10582			
Dimensional Stability	Length: 0.00%				ISO 23999			
	Width: 0.00%							
	Curling: 0.00%							
Abrasion Rating	Group P				EN 660-2			
Residual Indentation	0.1mm				EN 433			
Castor Chair	No Damage				EN 425			
Impact Sound Reduction	Ln,W 58				ISO 10140-3			
	IIC 52				ASTM E492-09			
	Product tested over Damtec 2.0mm Colour Underlay							
Light Fastness	≥ 6				EN ISO 105-B02			
Light Reflectiveness Values	180 Mayfair	17.92%	185 Camden	12.5%	350 Paddington	28.58%		
	510 Westminster	39.15%	520 Park Lane	24.29%	530 St James	23.8%		
	540 Imperial	19.63%	545 Colonial Blackbutt	30.73%	555 Colonial Spotted Gum	18.15%		
	560 High Street	29.82%	625 Marble Arch	19.7%	640 Fleet Street	14.11%		
	710 Lancaster	47.63%	730 Notting Hill	19.89%	750 Kensington	20.16%		
	780 Oxford	8.36%						
	Slip Resistance	P2				AS/NZ 4586		
	Residential Warranty*	25 Years						
Commercial Warranty†	10 Years							
Reaction to Fire	CRF 11 kW/m <sup>2</sup> Smoke Value 58%.min				EN ISO 9239			
Suitable for wet areas	Yes - subject to proper installation and maintenance							
Recommended Adhesive	Refer to Godfrey Hirst Adhesive Guide <a href="http://www.godfreyhirst.com">www.godfreyhirst.com</a>							

**Sustainability**

VOC Rating	Passes CETEC VOC test
Accreditation	Manufactured under a management system certified as complying with ISO 9001 & ISO14001

All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All Godfrey Hirst Floors Vinyl Plank products must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Floors Vinyl Plank Installation Instructions.

\*These residential warranties are in addition to any rights consumers may have under Australian consumer laws. Conditions apply: For full information in respect to the scope and limitations of these warranties, this must be read in conjunction with the Godfrey Hirst Vinyl Plank Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst vinyl plank products) available from your retailer, by calling 1300 444 778, or by download from [www.godfreyhirst.com](http://www.godfreyhirst.com).

†Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst account manager. Test results and certificates are available on request.