

Signature[®]
signaturefloors

Quattro
Hybrid Flooring



OAKS, AUSSIE SPECIES & TILES



WATER-PROOF LUXURY FLOORS
FEATURING AN EASY TO INSTALL
5G CLICK-SYSTEM

Oaks

Aussie Species

Tiles



Bristle Oak QUATTRO10	Sherwood Oak QUATTRO09	Styx Oak QUATTRO08	Talla Oak QUATTRO02	Brown Stringybark QUATTRO04	Mallee Spotted Gum QUATTRO01	New England Black Butt QUATTRO03	Argento QUATTRO07	Natural QUATTRO06	Urban Grey QUATTRO05
---------------------------------	----------------------------------	------------------------------	-------------------------------	---------------------------------------	--	--	-----------------------------	-----------------------------	--------------------------------

TECHNICAL SPECIFICATIONS

Plank Size	228 x 1520mm
Total Thickness	6mm (4mm board & 1.50mm backing)
Wear Layer	0.50mm
Wear Layer Treatment	Quartz enhanced PUR coating
Surface	Natural embossed, true to life oak boards
Edge Design	Micro V groove 4 sided

Fire Rating ISO 9239.1	Suitable all areas
Slip Rating	P3
Underfloor Heating	Suitable for water based systems
Planks per Box	6 pcs/box (2.08m ²)
Installation Method	5G - no underlay required
Warranty	25 Yr Residential, 10 Yr Commercial

- installs directly over irregularities and existing floors
- can be laid over ceramic and porcelain tiles
- can be laid over concrete
- can be laid over chipboard and tongue & groove flooring
- existing floors need to adhere to the sub-floor
- existing floor cannot be cushioned
- uneven floors require sub-floor preparation when there is a height variation more than 3mm over 1m*
- sub-floors should be clean and dry

* Please refer to installation guidelines; if uncertain see clarification prior.

